



FEATURES

01 **Dual 15 GAL Tanks**

> 30 gallon spray capacity, featuring new, lighter color tanks for improved liquid visibility.

O2 Up to 8' Adjustable Spray Width

Stainless steel breakaway boom with hidden plumbing. Nozzles are easy to reach and change-no special tools required.

O3 75' Hose Reel

CoxReels® 75' hose reel is perfect for spot spraying and long enough to access hard-to-reach areas.

O4 120 LB Hopper Capacity

120-lb hydraulic-driven Spyker® granular system.

O5 Dual High-Density Poly Fertilizer Trays

Adds 100 LBS of additional granular capacity.

O6 Up to 25' Variable Spread Width

Stainless steel side deflector offers increased perimeter efficiency and directional control.

O7 Stainless Steel Frame

Heavy-duty stainless steel chassis is long-lasting and durable to withstand long-term commercial use.

O8 5 GAL Fuel Capacity

Fuel tank holds up to 5 gallons of fuel.

O9 23.5 HP Engine

Now featuring the Kawasaki® FX730V 4-stroke, 90-degree V-twin vertical shaft engine with 23.5 horsepower and built-in 30 amp charging system. (21 HP Vanguard® engine option available)

10 Up to 10 MPH Transport Speed

> Reduce time traveling between properties and back and forth for fill-ups.

11 22" Rear Wheels

> 22" commercial grade turf tires provide additional hillside stability. *Dual drum parking rear brake.

12 120,000 SQ. FT. Per Fill

Based on using ¼ gallon spray nozzles.

13 **Foot-Activated Parking Brake**

> For brakes that hold (even on hills), our wheel motors have integrated drum brakes on both sides.